



FIRE SAFETY EQUIPMENT

Extinguishers / Extinguishing agents / Cylinders / Accessories

COMPANY & PRODUCT COLLECTION



Portable dry powder



Wheeled dry powder



Portable water-based



Wheeled water-based



Portable CO2



Wheeled CO2



Suspended dry powder



Superfine dry powder



Stainless steel



Lithium-battery portable



Lithium-battery wheeled



Wet chemical



AFFF foam



AFFF / AR foam



Synthetic foam



Synthetic / AR foam



Water-based agents



Wet chemical agent



Lithium-battery agent



Class A foam agent



Dry powder cylinders



CO2 cylinders



Water-type cylinders



Valves & accessories

YINGCHENG FIRE SAFETY

Equipment. Agents. One point of contact.

Fire extinguishers, extinguishing agents, cylinders and accessories for distributors, importers and project buyers.



01 EXTINGUISHERS

Portable, wheeled and suspended configurations.

02 EXTINGUISHING AGENTS

Foam, water-based and specialist agent options.

03 COMPONENTS

Cylinders, valves and matching accessories.

MANUFACTURING

Inside production.

Cylinder processing, assembly, finishing and product inspection.



Factory exterior · branding presentation



Cylinder processing



Assembly



Finishing & packing

Exterior signage is digitally adapted for brand presentation.

THE COLLECTION

Find your range.

Dry powder · portable & wheeled	05–06
Water-based · portable & wheeled	07–08
Carbon dioxide · portable & wheeled	09–10
Suspended · standard & superfine	11–12
Stainless steel	13
Lithium-battery series & wet chemical	14–16
Cylinders & accessories	17–18
Extinguishing agents	19–24
Packing, filling & storage	25–27
Ordering & product index	28–30
Contact	31–32

PORTABLE SERIES

Dry powder extinguishers.

Portable dry powder range: 0.5–12 kg. Selected model references are listed below.



YING CHENG

Model	Nominal charge	Catalogue rating
MF/ABCE1	1 kg	1A/21B/C/E
MF/ABCE2	2 kg	1A/21B/C/E
MF/ABCE3	3 kg	2A/55B/C/E
MF/ABCE4	4 kg	3A/89B/C/E
MF/ABCE5	5 kg	3A/89B/C/E
MF/ABCE6	6 kg	3A/113B/C/E
MF/ABCE8	8 kg	4A/144B/C/E

New series: ABC dry powder; operating temperature -30 to +60°C. Ratings follow the source catalogue.

MOBILE SERIES

Wheeled dry powder.

Wheeled configurations in 20 / 25 / 35 / 50 kg formats.



Model	Nominal charge	Catalogue rating
MFT/ABCE20	20 kg	6A/183B/C/E
MFT/ABCE35	35 kg	10A/233B/C/E
MFT/ABCE50	50 kg	10A/233B/C/E

Additional series: nitrogen propellant; catalogue test pressure 2.1 MPa.

PORTABLE SERIES

Water-based extinguishers.

Compact and portable configurations with water-based extinguishing agent.


PORTABLE RANGE

980 mL compact format
 2 / 3 / 6 / 9 L portable
 models

Model and application requirements
 are reviewed for each order.

Model	Nominal charge	Catalogue rating
MSWJ980	980 mL	0.5A/13B/E/5F
MS/ABEF2	2 L	1A/55B/E/5F
MS/ABEF3	3 L	1A/70B/E/5F
MS/ABEF6	6 L	2A/89B/E/25F
MS/ABEF9	9 L	3A/113B/E/40F

Temperature range: MSWJ980 +5 to +55°C; other listed portable models +5 to +60°C.

WHEELED SERIES

Water-based. Larger capacity.

Trolley-mounted configurations for buyers specifying a larger agent charge.



25 / 45 / 65

LITRE FORMATS

Water-based agent
Nitrogen propellant
Hose and trolley configuration

Model	Nominal charge	Catalogue rating
MSTW/ABEF25	25 L	4A/183B/E/75F
MSTW/ABEF45	45 L	6A/233B/E/75F
MSTW/ABEF65	65 L	10A/297B/E/75F

Catalogue operating temperature +5 to +60°C; test pressure 2.1 MPa.

CO2 COLLECTION

Carbon dioxide extinguishers.

CO2 collection: MT2 / MT3 / MT5 / MT6 / MT7 / MT10 / MT24. Portable MT/BE models below.



YING CHENG

Model	Nominal charge	Catalogue rating
MT/BE2	2 kg	21B/E
MT/BE3	3 kg	21B/E
MT/BE5	5 kg	34B/E
MT/BE7	7 kg	55B/E

Additional series: CO2 purity 99.9% minimum; catalogue temperature range -30 to +60°C.

WHEELED CO2

Mobile CO2 configurations.

Larger cylinder formats with trolley, hose and discharge assembly.



24 / 30
kg • NOMINAL CHARGE

Model	Nominal charge	Catalogue rating
MTT/BE24	24 kg	70B/E
MTT/BE30	30 kg	89B/E

Catalogue test pressure 22.5 MPa; confirm the required cylinder and approval specification.

AUTOMATIC CONFIGURATION

Suspended dry powder.

4.5 / 6 / 8 / 10 / 12 kg options and the models listed below.



Shown: FZX/APT4/1.2 · 4 kg

Model	Nominal charge	Coverage reference*
FZX/APT4/1.2	4 kg	1.13 sq. m
FZX/APT6/1.2	6 kg	1.33 sq. m
FZX/APT8/1.2	8 kg	2.01 sq. m
FZX/APT10/1.2	10 kg	3.14 sq. m

*Coverage values are source-catalogue references, not a system design. Installation suitability requires review.

AUTOMATIC CONFIGURATION

Superfine dry powder.

FZX/ACT series · 4 / 6 / 8 / 10 kg formats.



Shown: FZX/ACT4/1.2 · 4 kg

Model	Nominal charge	Coverage reference*
FZX/ACT4/1.2	4 kg	1.33 sq. m
FZX/ACT6/1.2	6 kg	3.14 sq. m
FZX/ACT8/1.2	8 kg	3.8 sq. m
FZX/ACT10/1.2	10 kg	5.42 sq. m

*Coverage values are source-catalogue references, not a system design. Installation suitability requires review.

COMPACT SERIES

Stainless steel extinguishers.

Compact stainless steel options in 0.5 / 1 / 2 kg formats.



YING CHENG

Nominal capacities	Configuration
0.5 / 1 / 2 kg	Agent and marking by agreed specification

Specify the intended application, agent type and destination-market requirements.

SPECIALIST PORTABLE SERIES

Lithium-battery extinguishers.

Water-based agent configurations offered in portable formats.



3 / 6 / 9

LITRE FORMATS

Model	Nominal charge
MS/ABEFLi3	3 L
MS/ABEFLi6	6 L
MS/ABEFLi9	9 L

Battery chemistry, pack size and intended scenario must be matched to the applicable test evidence.

SPECIALIST WHEELED SERIES

Larger water-based units.

Trolley-mounted models in the lithium-battery product series.



25 / 45 / 65

LITRE FORMATS

Configuration	Nominal charge
Wheeled · 25 L format	25 L
Wheeled · 45 L format	45 L
Wheeled · 65 L format	65 L

Model designation to be confirmed. Catalogue temperature range +5 to +60°C.

ADDITIONAL CONFIGURATIONS

Wet chemical & lithium-battery options.

Wet chemical and lithium-battery extinguisher configurations.



Wet chemical

Agent, capacity and discharge configuration on request.



Lithium-battery series

Model-specific specifications and test information on request.

Product photographs show configurations; no capacity or approval is inferred from appearance.

COMPONENT RANGE

Cylinders for your specification.

Dry powder, carbon dioxide and water-type cylinder options.



YING CHENG

Dry powder

Foot-ring / point-bottom



YING CHENG

Carbon dioxide

Model-specific configurations



YING CHENG

Water-type

Including internally coated options

Specify capacity, material, dimensions, neck thread and coating.

COMPONENT RANGE

Valves. Gauges. Accessories.

Matching parts for extinguisher assembly and procurement.



Valves · pressure gauges · hoses · siphon tubes · mounting components

Send a drawing, sample reference or matching extinguisher model.

AGENT COLLECTION

Foam & water-based agents.

An expanded selection of extinguishing agents and specialist formulations.



AFFF and alcohol-resistant AFFF	20-21
Synthetic and alcohol-resistant foam	22
Multifunctional water-based agents	23
Wet chemical / lithium-battery / Class A	24

Agent selection requires the applicable technical data, compatibility and destination requirements.

FOAM CONCENTRATE

Aqueous film-forming foam.

AFFF concentrates in 3% and 6% nominal proportioning formats.



Series	Nominal proportion
AFFF	3%
AFFF	6%

Request the exact formulation, TDS, SDS, application data and relevant destination requirements.

FOAM CONCENTRATE

Alcohol-resistant AFFF.

Alcohol-resistant AFFF concentrate model families.



Series	Nominal proportion
AFFF/AR	3%
AFFF/AR	6%

Confirm fuel compatibility, system compatibility and the selected formulation before purchase.

FOAM CONCENTRATE

Synthetic foam families.



Synthetic foam

Alcohol-resistant

Series	Nominal proportion
S·synthetic foam	3% / 6%
S/AR·alcohol-resistant synthetic foam	3% / 6%

No fluorine-free or environmental certification claim is inferred from the product family name.

EXTINGUISHING AGENTS

Multifunctional water-based agents.



Source references	Additional variants
S-3-(-30°C, 0°C)-AB	S-3-AB
S-6-(-18°C, 0°C)-AB	S-10-AB
S-10-(-10°C, 0°C)-AB	S-100-AB
S-100-(-25°C)-AB	S-100-(-35°C)-AB

Reference text identifies catalogue variants; operating and storage limits require the technical data sheet.

EXTINGUISHING AGENTS

Specialist agent options.

Additional formulations for review against the intended application.



环保型——A类（压缩空气）
泡沫灭火剂 MJABP

Product family	Reference
Wet chemical agent	Cooking-oil application series
Lithium-battery extinguishing agent	Model-specific formulation
Class A foam agent	MJABP·compressed-air foam series

Ask for product-specific TDS, SDS and supporting test information.

AGENT OPERATIONS

Bulk packing & storage.



IBC container storage

Packaging format, net quantity and shipping details are confirmed in the quotation.

PACKING & HANDLING

Filling and drum formats.



Filling & packed containers



Drum packing & storage

WAREHOUSE VIEWS

Organised for handling.



Warehouse and packed-material storage.

WORKING WITH YINGCHENG

Start with the specification.

01 Define the product

Product family, model, capacity or agent formulation; quantity and destination.

02 Agree the configuration

Technical requirements, accessories, packaging and brand marking.

03 Review the documents

Model-specific data, relevant approvals and inspection requirements.

04 Confirm the order

Commercial terms, production schedule, delivery and shipping documents.

BEFORE QUOTATION

The details that matter.

Extinguishers

Model / nominal charge / application / destination / required approval / hose and valve / labelling.

Extinguishing agents

Formulation / concentrate percentage / required test data / packaging / quantity / destination.

Cylinders & parts

Material / dimensions / neck thread / coating / drawing or reference / matching assembly.

Catalogue values describe listed variants. Final supply is governed by the agreed model specification.

QUICK REFERENCE

The expanded collection.

Portable dry powder / wheeled dry powder	05 / 06
Portable water-based / wheeled water-based	07 / 08
CO2 collection / wheeled CO2	09 / 10
Suspended standard / superfine	11 / 12
Stainless steel / specialist extinguishers	13–16
Cylinders / valves and accessories	17 / 18
AFFF / AFFF-AR / synthetic foam	20–22
Water-based / specialist agents	23 / 24

ABOUT THIS COLLECTION

Product labels with YINGCHENG artwork are brand-layout examples. Final labels, model markings and technical claims follow the agreed specification. Source fire-class designations are retained as catalogue references; no equivalence to a destination-market rating is implied.

SPEAK WITH US

Tell us what you need.

Steven Mao

FOUNDER

WHATSAPP / MOBILE

+86 19168079849

EMAIL

steven@yingchenging.com

TELEPHONE

+86 (21) 58877585

WECHAT

cc02081314M

WEBSITE

www.ycfiresafety.com



Scan for WhatsApp

Ying Cheng Stable and Prosperous Industrial Development (Shanghai) Co., Ltd.

Office: Room 439, Building 1, Jinqiaogu Creative Park, No. 2216 Jingao Road, Pudong New Area, Shanghai, China 201206.

Company address: No. 6, Lane 129, Huajiang Road, Jiading District, Shanghai, China.



YOUR NEXT ORDER STARTS HERE.

Extinguishers.

Extinguishing agents.

Cylinders & accessories.



Contact Steven Mao

+86 19168079849

www.ycfiresafety.com

SHANGHAI, CHINA